CSA C22.1:21

Canadian Electrical Code, Part I

Safety Standard for Electrical Installations

2021
25th Edition

Standards Council of Canada
Conseil canadien des normes

REVISED MARCH 2021

Legal Notice for Standards

Canadian Standards Association (operating as "CSA Group") develops standards through a consensus standards development process approved by the Standards Council of Canada. This process brings together volunteers representing varied viewpoints and interests to achieve consensus and develop a standard. Although CSA Group administers the process and establishes rules to promote fairness in achieving consensus, it does not independently test, evaluate, or verify the content of standards.

Disclaimer and exclusion of liability

This document is provided without any representations, warranties, or conditions of any kind, express or implied, including, without limitation, implied warranties or conditions concerning this document's fitness for a particular purpose or use, its merchantability, or its non-infringement of any third party's intellectual property rights. CSA Group does not warrant the accuracy, completeness, or currency of any of the information published in this document. CSA Group makes no representations or warranties regarding this document's compliance with any applicable statute, rule, or regulation.

IN NO EVENT SHALL CSA GROUP, ITS VOLUNTEERS, MEMBERS, SUBSIDIARIES, OR AFFILIATED COMPANIES, OR THEIR EMPLOYEES, DIRECTORS, OR OFFICERS, BE LIABLE FOR ANY DIRECT, INDIRECT, OR INCIDENTAL DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES, HOWSOEVER CAUSED, INCLUDING BUT NOT LIMITED TO SPECIAL OR CONSEQUENTIAL DAMAGES, LOST REVENUE, BUSINESS INTERRUPTION, LOST OR DAMAGED DATA, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSS, WHETHER BASED IN CONTRACT, TORT (INCLUDING NEGLIGENCE), OR ANY OTHER THEORY OF LIABILITY, ARISING OUT OF OR RESULTING FROM ACCESS TO OR POSSESSION OR USE OF THIS DOCUMENT, EVEN IF CSA GROUP HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, INJURY, LOSS, COSTS, OR EXPENSES.

In publishing and making this document available, CSA Group is not undertaking to render professional or other services for or on behalf of any person or entity or to perform any duty owed by any person or entity to another person or entity. The information in this document is directed to those who have the appropriate degree of experience to use and apply its contents, and CSA Group accepts no responsibility whatsoever arising in any way from any and all use of or reliance on the information contained in this document.

CSA Group is a private not-for-profit company that publishes voluntary standards and related documents. CSA Group has no power, nor does it undertake, to enforce compliance with the contents of the standards or other documents it publishes.

Intellectual property rights and ownership

As between CSA Group and the users of this document (whether it be in printed or electronic form), CSA Group is the owner, or the authorized licensee, of all works contained herein that are protected by copyright, all trade-marks (except as otherwise noted to the contrary), and all inventions and trade secrets that may be contained in this document, whether or not such inventions and trade secrets are protected by patents and applications for patents. Without limitation, the unauthorized use, modification, copying, or disclosure of this document may violate laws that protect CSA Group's and/or others' intellectual property and may give rise to a right in CSA Group and/or others to seek legal redress for such use, modification, copying, or disclosure. To the extent permitted by licence or by law, CSA Group reserves all intellectual property rights in this document.

Patent rights

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights. CSA Group shall not be held responsible for identifying any or all such patent rights. Users of this standard are expressly advised that determination of the validity of any such patent rights is entirely their own responsibility.

Authorized use of this document

This document is being provided by CSA Group for informational and non-commercial use only. The user of this document is authorized to do only the following:

If this document is in electronic form:

- load this document onto a computer for the sole purpose of reviewing it;
- search and browse this document; and
- print this document if it is in PDF format.

Limited copies of this document in print or paper form may be distributed only to persons who are authorized by CSA Group to have such copies, and only if this Legal Notice appears on each such copy.

In addition, users may not and may not permit others to

- alter this document in any way or remove this Legal Notice from the attached standard;
- sell this document without authorization from CSA Group; or
- make an electronic copy of this document.

If you do not agree with any of the terms and conditions contained in this Legal Notice, you may not load or use this document or make any copies of the contents hereof, and if you do make such copies, you are required to destroy them immediately. Use of this document constitutes your acceptance of the terms and conditions of this Legal Notice.

Revision History

CSA C22.1:21, Canadian Electrical Code, Part I

Administrative update — March 2021
Index added.

The following is a list of revisions, additions and deletions to CSA C22.1:21:

Administrative update — March 2021

 © 2021 Canadian Standards Association

Index

A

AC module, 64-002, 64-106, 64-110
Acceptable, definition of, Section 0
Accessibility
    disconnecting means, 28-604
    junction boxes, 12-3014
    maintenance, 2-314
    overcurrent devices, 6-206, 14-106
Accessible
    as applied to equipment, 2-308, 6-206, 14-406, 30-708, Section 0
    as applied to wiring methods, 12-2500, 12-3032, 18-152, 18-252, Section 0
Accredited certification organization, Section 0
Actual primary current, 42-002, 42-014
AFCI *See* Arc-fault circuit interrupters
Air conditioners *See* Hermetic equipment
Air ducts and plenums, conductors in, 12-010, 16-220, 54-406, 56-210, 60-314, 60-402, Table 19
Aircraft hangars, 20-400
Airport installations, Section 74
Aluminum-sheathed cable, 2-126, 4-030, 6-304, 12-700 to 12-718, Section 0
Amateur radio installations, Section 54
Amendments to the Code, Appendix C6, Appendix C7
Ampacity
    cables, 16-330, Table 12E
    conductors, 4-004, 4-034, 16-210, 16-330, Tables 1, 2, 3, 4, 12, 12A, 57, 66, D8A to D11B
        motor feeder, 28-110
        motor secondary insulated, 28-112
        motor, 28-104 to 28-108
        motor compressor, 28-706
    correction factors, Table 5A, 5B, 5C, 5D
    definition of, Section 0
    neutral supported cable, 4-004, Tables 36A, 36B
    power cables, Table 12A
    wires and cables, 4-004
Amplifiers, 54-500, 54-1006, 68-062
Amusement park, Section 66
Amusement ride, 66-002, 66-100
Anaesthetizing location, 24-002, 24-204, 24-208
Anchoring material to masonry and concrete, 2-114
Antenna, community distribution, Section 54
Antennas, grounding of, 54-922
Appliances, electric heating and cooking, 26-740 to 26-750
Application Class A photovoltaic module, 64-002, 64-208
Application Class B photovoltaic module, 64-002, 64-208
Application Class C photovoltaic module, 64-002, 64-208
Applied part, 24-002
Approved, definition of, Section 0

 © 2021 Canadian Standards Association

Arc-fault circuit interrupters
combination-type, 26-650, 26-658
outlet branch-circuit-type, 26-650, 26-658
Arc-fault protection, 26-650, 64-210
branch circuits for dwelling units, 26-658
Arc flash protection, 2-306
Armour, definition of, Section 0
Array, 64-002, 64-204, 64-210, 64-218
Authority for Rules, 2-000
Authorized person, definition of, Section 0
Auxiliary grounding electrode, 64-002, 64-316, 64-412
Auxiliary gutters, 12-1900 to 12-1904, Section 0
AWG, Section 0
sizes of conductors, 2-120

B

Ballast load, 64-002, 64-500
Barbed wire, 26-306
Bare conductor, 12-1802, 12-2600, 36-100, 36-106, 36-108, 36-110, Section 0
Bare element water heater, 62-102, 62-408
Bare or covered conductor ampacities, Table 66
Basic care area, 24-002, 24-100
bonding to ground in, 24-104
circuits in, 24-102
other equipment in, 24-108
receptacles in, 24-106
Basic load, 8-002, 8-200 to 8-210
Bathroom, Section 0
Battery, 14-308, 46-202, 64-002, 64-802, 64-804, 64-820
charging equipment, 20-112, J20-112
installation, 64-800 to 64-820, 64-920
sealed cell *see* Sealed cell battery
Battery-based micro-hydropower system, 64-002, 64-510
Bipolar system, 64-002, 64-056, 64-064
Boathouse, 78-002, 78-100 to 78-102
Bodies of water, 26-956
Body contact, 24-002
Bonding, 10-500 to 10-506, Section 0
cable trays, 12-2208
capacitors, 26-206
connections for alternating current systems, 10-210
equipment, 10-600 to 10-616
equipotential, 10-700 to 10-708
elevator equipment, 38-082, 38-083
equipment, 10-600, 32-104, 34-110, 54-302, 54-504, 54-900 to 54-922, 68-402
in hazardous locations, 18-074, J18-072
non-electrical equipment, 10-700, 68-058
objectives, 10-002
patient care areas, Section 24

 © 2021 Canadian Standards Association

pools, 68-058
signs, 34-110
Bonding conductor, definition of, Section 0
Bottom shield, 12-802, 12-812
Boundary fence, 36-002, 36-312
Box connector, Section 0
Boxes
in concrete construction, 12-3008
outlet, 12-3000, 30-304, 30-408
pull, sizes of, 12-3036
unused opening, 12-3024
Boxes and cabinets
conductors in, 12-3030
entrance of cables, 12-3022
Boxes and fittings, 12-524, 12-3012
Branch circuit, 8-300 to 8-304, Section 0
capacity, 30-712
heating device, 62-110
overcurrent devices, 8-108
Building, definition of, Section 0
Bulk storage plants, 20-200 to 20-212
Bus, definition of, Section 0
Busbar, 12-2302, 12-2600, 24-104, 64-112
bare, use of, 12-2600
support, 12-2302
Busway, 12-2000 to 12-2020, Section 0

C

Cabin, 58-002, 58-200
Cabinet, definition of, Section 0
Cabinet lighting system, 30-002, 30-1208
Cable, Section 0
aluminum-sheathed, 2-126, 4-030, 6-304, 12-700 to 12-718, Section 0
armoured, 12-600, 12-602
between boxes and fittings, 12-510, 12-618
concealed armoured, 12-616
continuity of armoured, 12-608
corrosion protection, 2-116, 12-100, 12-708
dimensions of DLO cable, Table 10D
ducts and plenum, 12-010, 16-220, 54-406, 56-210, 60-314, 60-402
embedded, 12-512, 12-704, 12-932, 12-938
flat systems, 12-1614
in roof decking systems, 12-022
messenger, 30-1116, 30-1118
metal-covered, 18-060
mineral-insulated, 6-304, 12-700, 12-706
neutral supported, 12-318, Tables 36A, 36B
non-metallic-sheathed, 12-500 to 12-526
portable power, 4-034

 © 2021 Canadian Standards Association

protection for, 12-518, 12-604, 12-710
radii of bends, 12-614, 12-712, 36-102, Table 15
sheathed, joints in, 36-114
terminating
armoured, 12-610
facilities, 36-112
mineral-insulated, 12-714
travelling, 38-011, 38-012, 38-041, 38-044, 58-102, 58-200, 58-202, 60-312
types of, 12-100
where outlet boxed are not required, 12-522
Cable bundle, 16-310, 16-330, 66-454
Cable distribution plant, 54-002, 54-102
Cable gland, 18-002, 18-102, 18-152, 18-192, 18-196, 18-202, 18-252, 62-104, J18-002, J18-106, J18-108, J18-152, J18-204
Cable lighting system, 30-002, 30-1206
Cable ties, 12-510, 12-706, 12-1010, 12-1308, 12-1504
Cable tray, 12-2202, Section 0
connection to other wiring methods, 12-2206
correction factors, Table 5D
installation, 12-2200
intrinsically safe or non-incendive electrical equipment, 18-066
joints and splices within, 12-2204
provisions for bonding, 12-2208
Cablebus, 12-2250 to 12-2258, Section 0
Class A, 12-2252
Class B, 12-2252
Calculated load, 8-002, 8-104, 8-106, 8-202, 26-258
Capacitors, 26-200 to 26-222
conductor size for, 26-208
diagnostic imaging equipment, 52-010
disconnecting means, 26-212
drainage of stored charge, 26-222
grounding of, 26-206
guarding of, 26-204
indoors, 26-010, 26-202
motor circuits, 26-218
overcurrent protection, 26-210
transformer supplying, 26-220
Carbon monoxide alarms, 32-200
Cardiac contact, 24-002
Carnivals, Section 66
Casual contact, 24-002
Cathodic protection, Section 80
Caution marking, 2-102, Appendix M
Cell, 64-002
definition of, Section 0
Cellular floor, 12-1800 to 12-1820
definition of, Section 0
Cellular floors, 12-1800 to 12-1820

Cellulose nitrate film storage, 26-360 to 26-368
Central unit, 62-102
    installation of, 62-206
Charge controller, 64-002, 64-060, 64-064, 64-066, 64-216, 64-818, 64-924
Circuit breaker, 14-300 to 14-308, 26-120, Section 0
    instantaneous-trip, 28-210
Circuits
    capacity, 30-712
    Class 1, 16-100 to 16-118
    Class 2, 16-200 to 16-226
    classifications, 16-002
    communication cables, 16-012
    control for diagnostic imaging equipment, 52-012
    heating device, 62-110, 62-114
    loading, 8-104
    overcurrent trip coils for circuit breakers, Table 25
    safety control devices, 16-010
Class 1 circuits, 16-100 to 16-118
Class 2 circuits, 16-200 to 16-226
Class 2 power and data communication circuit, 16-000, 16-012, 16-210, 16-300 to 16-350, 16-310, Table 60
Clearances
    minimum, Tables 30 to 34
    of equipment, 26-302
    of insulated conductors and cables,
    of insulated conductors and cables, 12-310
    working, 38-005
Combination inverter/power conditioning unit (PCU), 64-002, 64-112, 64-204, 64-212
Combination-type arc-fault circuit interrupter, 26-650, 26-658
Combustible dust, 18-002, 18-050, J18-002
Combustible flyings, 18-002, J18-002, J18-008
Combustible gas detection equipment, 18-070
Combustible surfaces, equipment over, 26-004
Communication circuits, 16-012, 60-108, 60-204, 60-504
Communication conductors, 60-300, 60-308
    in ducts and plenum chambers, 60-314
    under raised floors, 60-318
    separation, 60-308
    underground, 60-600 to 60-604
Communication flat cable, 60-322
Communication system, Section 0
Community antenna distribution system, 54-004, 54-100 to 54-108, Section 0
Compressed natural gas refuelling stations, 20-060 to 20-070
Concealed, definition of, Section 0
Concession, 66-002, 66-202, 66-304
Condensation in consumer's service raceway, 6-312
Conditional branch, 24-002, 24-302, 24-304
Conductive dust, 18-002, J18-002
Conductor ampacities, 4-004, 4-034, 16-330, Tables 1, 2, 3, 4, 12, 12A, 57, 66, D8A to D11B

 © 2021 Canadian Standards Association

motor, 28-104 to 28-112
Conductor colour coding, 4-032
luminaire, 30-402
Conductor size, 38-012
grounding, 36-300, 36-308 to 36-312, Tables 16, 41, 43
motor, 28-104 to 28-112, Table D16
Conductor space in boxes, 12-3034, 12-3036, Tables 22, 23
Conductor supports, 12-306
Conductors, Section 0
air ducts and plenums, 12-010, 16-220, 60-314, Table 19
auxiliary gutters, 12-1904
bare, supporting of, 36-106
boxes and cabinets, 12-3030 to 12-3036, Tables 22
Class 2, in a vertical shaft or hoistway, 16-218, 54-402, 60-312
Class 1 circuits, 16-112, 16-114
Class 2 circuits, 16-210, 16-212
clearance of, 12-310, 12-506, 36-108, 36-110, Tables 30 to 34
common neutral, 4-020
communication, 60-300, 60-304
conditions of use of, Table 19
contact, for cranes and hoists, 40-010 to 40-016, 40-022
designations and voltage ratings, Table D1
different systems, 12-106, 16-114, 60-308
dimensions, Tables 10A, 10B, 10C
elevator shafts, 36-116
entrance into boxes, 12-3022
feeder, for motors, 28-110
fire alarms, 32-100
flame-tested covering, 12-104
flat, 12-800, 60-322
grounding, 10-116, 10-210
guarding of contact, 40-020
guarding of live parts, 36-110
height of, 30-1106, Tables 33, 34
hoistways, 12-014, 16-218
identification of neutral, 4-024, 4-026, 4-028, 4-030
insulated, 12-102, 12-316, 28-106
insulation, 38-011
for luminaires, 30-404
of neutral, 4-016
rating correction factor, Table 12C
resistance, 70-130, Table 24
in conduit and tubing, 12-910
in raceways, 12-904
joints, 12-112, 36-114
joints in contact, 40-016
mechanical damage, 12-304, 12-514 to 12-518
number of, 12-1120, 12-1160, 12-1218, 12-1304
in boxes, 12-3034, Tables 22, 23

in raceways, 12-910, 12-1714, 12-2104
one enclosure, 12-904
outdoor luminaires, 30-1102
overhead supply service, 6-112
in parallel, 10-612, 12-108, 12-904
pendant lampholders, 30-608
protection of, 40-004, 40-006, Table 53
overcurrent, 14-100
underground, 12-012, Table 53
in raceways, 12-904, 12-908, 12-1606, 44-104
radii of bends in, 12-110, 12-614, 36-102, Table 15
reduction in size of, 14-100, 28-110
rigid RTRC conduit, 12-1212
secondary, for motors, 28-112
separation, 60-308
services, 6-300, 6-302
in crawl spaces, 6-208
outside building, 6-208
shielding, 36-104
size, 4-002, 38-012
AWG, 2-120
for capacitors, 26-208
fault current, 36-308
fault currents, 36-308, Table 51
neutral, 4-018
overhead, 12-308
transformers, 26-256, 26-258
spacing of, 12-204, 30-1110, 36-108, Tables 30, 31, 32
from combustible material, 30-1108
supply
for arc welders, 42-006
for cranes and hoists, 40-002, Table 58
for resistance welders, 42-014, Table 42C
supplying motors, 28-100 to 28-112, Table 37
supporting of, 12-120, 12-206
temperature, 4-004, 4-006
temperature limitations, 4-006
terminating services, 6-114
termination of, 12-116, 12-118, 36-112
track as, 40-018
types of, 12-302, 12-902
unused ends of, 12-114,
use of, 12-402, Table 11
identified, 4-030
multi-, 12-106
single-, 4-008, 12-106, 12-108
vertical, supports for, 12-120, Table 21
vertical shafts, 16-218, 54-402
voltage between, 12-502

 © 2021 Canadian Standards Association

wireways, 12-2104
Conduit, Section 0
conductors in rigid RTRC, 12-1212
cross-section, 12-910, Tables 9A to 9H
expansion and contraction of, 12-1012, 12-1118
field bends in rigid PVC, 12-1108
fill, allowable, 12-910, Table 8
fittings
for rigid PVC, 12-1112
for rigid RTRC, 12-1208
flexible, 12-1000
installation, of rigid RTRC, 12-1206
internal diameter and cross-sectional areas, Tables 9A–9H
liquid-tight flexible metal, 12-1302 to 12-1308
heavy duty, 18-152
minimum size of, 12-1004
non-metallic, 12-1302
number of conductors in, 12-910, 12-1120, 12-1160, 12-1304
radius, Table 7
rigid, 12-1000
PVC, 12-1100 to 12-1124
RTRC, 12-1200 to 12-1220
Type AG, 12-1200, 12-1202, 12-1216
Type BG, 12-1200, 12-1202
Type XW, 12-1200, 12-1202, 12-1216, 18-152, 18-252
Types EB1 and DB2/ES2 PVC, 12-1150 to 12-1166
split straight, 12-1124, 12-1164
supports, 12-1010, 12-1114
temperature limits in rigid PVC, 12-1104
threads, 12-1006, 12-1008, 18-102, Table 40
use of
non-metallic, 12-518
rigid and flexible, 12-1002
rigid RTRC, 12-1204
Connections
to different circuits, 14-414
between different forms of wiring, 12-716, 12-2108
to heating terminals, 62-108
to identified terminals, 26-002
lampholders, 30-602
luminaires, 30-308
open wiring and raceways, 12-926
other systems, 12-716, 12-2002, 12-2108
portable motors, 28-102
to supply circuit, 52-006
Connector, 10-614, 12-116, 12-618, 12-714, 12-2204, 12-2302, 12-2316, 12-3022, 12-3034, 22-108, 30-308, 64-220, 66-400, 66-456, 86-306
Container refill centre (propane service station), 20-030, 20-032, 20-034, J20-032, J20-034
Continuous duty, definition of, Section 0

 © 2021 Canadian Standards Association

Continuous duty service, 28-010, 28-106, 28-108, 28-112
Continuous positive pressure ventilation, 22-700, 22-704
Control
diagnostic imaging equipment circuits, 52-012
equipment, 28-712
luminaires, 30-710, 30-804
from more than one point, 14-604
motors, 28-500 to 28-506
remote control circuits, 14-608
Control circuit, 14-608, 16-116, 28-506, Section 0
Control devices
appliances, 14-602
connection of, 14-016
enclosures of, 14-410
grouping of, 14-412
indication, 14-408
location of, 14-406
rating of, 14-012, 14-400, 34-102
required, 14-010
temperature, 62-120, 62-202
used only for switching, 14-416
Controller, 12-3032, 28-500, 28-602, 28-604, 28-804, 28-806, 38-005, 38-013, 38-015, 38-051, 38-052, 38-071, Section 0
Cooking equipment, ventilation for, 26-750
Cord set, 12-402, 70-108, Section 0
Cords
flexible, J18-220, J18-270, J18-318, J18-368
ampacity of, 4-012, Table 12
in hazardous locations, 18-110, 18-158, 18-196
sizes of, 4-010
uses of, 12-402, Table 11
Corrosion protection, 2-116
Covered conductor, 4-004, Section 0, Table 66
Covers, outlet box, 12-3002, 30-304
Cranes, Section 40
Critical care area, 24-002, 24-100, 54-918, 60-408
bonding to ground in, 24-112
circuits in, 24-110
receptacles in, 24-114
Current monitoring devices, 6-212
Current-permit, 2-016, Section 0
Currents, sheath, 4-008, 12-106
Customer distribution circuit, 54-002, 54-102
Customer service enclosure, 54-002, 54-102
Cut-out box, definition of, Section 0
Cylindrical bushing, 12-516

D

Damage, 2-032

 © 2021 Canadian Standards Association

Damp location, 30-318, 30-320, 30-606, Section 0
Data processing systems, 12-020, 12-402, 26-1000, 60-316
branch circuits supplying, 8-302
Dead, as applied to electrical current, definition of, Section 0
Dead front, 44-200, Section 0
Decorative pool, 68-050, 68-060, 68-066
Deep well submersible pump, 26-950, 26-954
Definitions, Section 0
Degree of protection, 2-400, 18-002, 18-102, 18-152, J18-002, J18-152
Delayed vital branch, 24-002, 24-302, 24-304
Demand factors, 8-106, 8-400, 42-006, 42-012, Section 8, Table 62
heating device, 62-118
marinas, 78-054
service and feeder conductors, 72-102
use of, 8-106
Demonstrated load, 8-002, 8-106
Descriptive system document, 18-002, 18-066, Appendix F
Deviation from Code, 2-030
Diagnostic imaging equipment
bonding, 52-014
capacitors, 52-010
disconnecting means, 52-008
installations, Section 52
transformers, 52-010
Dielectric heating, 62-102, 62-406
Different systems, definition of, Section 0
Dimmers, theatre, 44-212
Disconnecting means, 14-702, 28-600, 30-308, 32-306, 36-214, 40-008, 64-060, 84-020 to 84-024, 86-304, Section 0
accessibility of, 28-604
capacitor feeders and branch circuits, 26-212
diagnostic imaging equipment, 52-008
elevators, 38-051
fused circuits, 14-402
generators, 28-900
grouping of, 14-414
heating equipment, 26-806, 26-808
individual poles, 30-1008
lampholders, 30-602
motor-compressor, 28-714
motors, 28-600 to 28-604
photovoltaic systems, 64-060
portable equipment, 28-602, 28-604
rating, 34-102
signs and outline lighting, 34-100
solid-state systems, 14-702
transformers, 26-248
welders, 42-010
wind turbine, 64-310

Disconnection, 2-304
Dispensing system, 20-032
Diversion charge controller, 64-002, 64-820, 64-926
Diversion load, 64-002, 64-510, 64-600, 64-604, 64-820
Diversion load controller, 64-002, 64-318, 64-922
Docking facility, 78-002, 78-100 to 78-102
Drainage
    consumer's service raceways, 6-300, 6-312
    equipment, 2-326
Drainage of capacitor charge, 26-222
Dry location, 12-1602, 12-2008, 12-2200, 12-2306, 12-2500, 16-222, Section 0
Dry-niche luminaire, 68-050, 68-066
Dry well, 22-700, 22-704
Dual process seal equipment, 18-002, J18-002
Dump load *see* Diversion load
Dump load controller, 64-002
Duplex receptacle
    definition of, Section 0
Dust, 18-002, 18-004, 18-008, 18-050, 18-054, 18-068, 28-016, 28-318
    explosive, 18-194, 18-204
Dust-tight, definition of, Section 0
Duty, definition of, Section 0
Duty cycle, 38-013, 42-002, 42-006, 42-012, 42-014, 42-020
Dwelling unit, 2-110, 8-200, 26-600, 26-602, 26-656, 26-658, 26-720, 26-722, 30-706, 30-802, 32-200, Section 0, Table 68

E

Electric elevator, 38-083, Section 0
Electric vehicle, 86-100, 86-400
Electric vehicle charging systems, Section 86
Electric vehicle connector, 86-100, 86-400
Electric vehicle energy management system, 8-002, 8-106, 8-500, 86-300
Electric vehicle supply equipment (EVSE), 86-100, 86-104, 86-200, 86-300, 86-302, 86-304, 86-306
    demand factors, Table 38
    locations, 86-400 to 86-404
Electric welders, Section 42
Electrical communication systems, Section 60
Electrical contractor, 2-004, 2-012, Section 0
Electrical equipment, Section 0, Section 26
    safety standards, Appendix A
    working space, Table 56
Electrical installation, Appendix G, Section 0
Electrical metallic tubing, 12-1400, Section 0
    connections, 12-1412
    minimum size, 12-1408
    number of conductors in, 12-1410
    radii of bends in, 12-924
    tubing supports, 12-1406
Electrical non-metallic tubing, Section 0

 © 2021 Canadian Standards Association

supports, 12-1504
Electrical supervision, 32-106
Electronic governor, 64-002, 64-510, 64-604
Electrostatic spraying, 20-308, 20-310
Elevator, Section 0
equipment, grounding of, 38-081, 38-082
feeder demand factors, Table 62
installations, 38-021
overcurrent protection, 38-061
wiring methods, 38-021
Elevator machinery, definition of, Section 0
Emergency electrical power supply system, 24-002, 24-304, 24-306
Emergency lighting, 8-212, 22-708, 46-300, Section 0
Emergency power
for elevators, 38-091
supply, 46-200 to 46-212
Emergency power supply, 46-002, 46-200 to 46-212, Section 46
capacity of, 46-100
instructions for, 46-102
maintenance of, 46-104
trouble signal devices, 46-210
types of, 46-202
unit equipment, 46-300
wiring methods for, 46-108
EMT *See* Electrical metallic tubing
Enclosures
control devices, 14-410
marking of, 2-402
signs, 34-200
types of, 2-400, Table 65
Energized, definition of, Section 0
Energized part, 64-202, 64-220, 64-804, 64-904, 64-928, Section 0
Energy storage system, 64-000, 64-002, 64-050, 64-074, 64-112, 64-900 to 64-928
Equipment
auxiliary, for luminaires, 30-708
change of marking on, 2-100
Class 1 circuits, 16-102
Class 2 circuits, 16-222
clearance, 26-302
combustible floors, 26-004
combustible gas equipment, 2-328
connections of diagnostic imaging equipment, 52-006
control of, 28-712
disconnecting means on portable, 28-604
drainage of, 2-326
ducts and plenums, 12-010, 16-220, 54-406, 56-210, 60-314, 60-402
equivalent zone and division group classifications, Table 18A
exposed to ingress of water
fences, 26-300 to 26-324

fusible, 26-142
grounding connections for, 10-402
hazardous locations, 18-050
heating, 26-800 to 26-808, Section 62
hermetic type, 28-700
horsepower rated, 28-704
illumination of, 2-320
installation
electrical equipment, 2-122
other than electrical equipment, 2-124
intrinsically safe, 18-066
liquid-filled
indoors, 26-010
outdoors, 26-012
location of service, 6-206
marking of, 2-100, 2-102
proximity of flammable materials, 2-322
rating, 28-704
rebuilt, 2-106
space for, 2-308
stages, 44-300 to 44-356
substitution of, 2-108
use of approved, 2-024
ventilation for, 2-324
work on live, 2-202
Equipment protection level (EPL), 18-002, 18-050, 18-090, 18-100, 18-150, Tables B18-5, JB-2
EPL Da, 18-002, J18-226, J18-276, J18-328, J18-378
EPL Db, 18-002, 18-200
EPL Dc, 18-002
EPL Ga, 18-002, 18-090
EPL Gb, 18-002, 18-100
EPL Gc, 18-002
Equipotential bonding, 10-700 to 10-708
Equipotentiality, 10-000, 10-002, 10-004, 10-100, 10-114, 10-212, 10-700
Essential electrical system, 24-002, 24-102, 24-106, 24-300 to 24-306
Exit signs, 46-400
Explosion-proof enclosure, 18-102, 18-104, 18-152, 18-154, Section 0
Explosion seal, 18-002, 18-104, 18-154, J18-002, J18-108, J18-154
Explosive atmosphere, 18-002, 18-050, 18-064, 18-066, Table 18
Explosive dust atmosphere, 18-002, 18-004
cable trays ins, 18-068, 18-190 to 18-254, J18-226, J18-276
locations containing, 18-008
Explosive gas atmosphere, 18-002, 18-004, 18-090 to 18-158, J18-002, J18-004
combustible gas detection equipment for use in, Appendix H
locations containing, 18-006
Exposed
as applied to live parts, Section 0
as applied to wiring methods, Section 0
Exposed plant, 60-100, 60-102, 60-200, 60-202

 © 2021 Canadian Standards Association

Extra-low voltage, 10-206, Section 0
lighting systems, 30-1200 to 30-1208
Extra-low-voltage power circuit, 16-004, 16-108, Section 0
Extra-low-voltage suspended ceiling power distribution system, 12-2300 to 12-2320, 12-2302

F

Factory-built homes and structures, Section 70
Farm buildings housing livestock, 22-800 to 22-808
Feeder conductors for motors, 28-110
Feeders, 4-022, 8-106, Section 0
calculated load, 8-200 to 8-212
Watts per square metre and demands factors, Table 14
Fees, 2-008
Fences
for equipment, 26-300
fabric, 26-312
gates, 26-310
grounding, 36-312
height, 26-304
posts, 26-308, 26-316
wooden, 26-314
Fiber optics, Section 56
Field-assembled energy storage system, 64-002, 64-900, 64-902, 64-904, 64-914, 64-920, 64-928
Field bends, 12-1108, 12-1156
Field bends in conduit, 12-1108, 12-1156
Filling plant (bulk plant), 20-030, 20-032, 20-034, J20-032, J20-034
Film-vaults, 26-362 to 26-368
Filters, zero sequences, 26-266
Finishing processes, 20-300 to 20-314
Fire alarm systems, 32-100
circuits in communication cables, 32-102
conductors, 32-100
control unit, 32-108
power supply, 32-108
transponder, 32-108
wiring, 32-102
Fire pumps, 32-300 to 32-312
Fire-resisting, 26-010, Section 0
Fire separation, penetration of, 60-310
Fire spread, 2-128
Fittings, terminal, 12-3004, 12-3006
Fixed electric heating systems, Section 62
Fixed pier, 78-100 to 78-102
Flame spread requirements, 2-130, 2-132
Flammable fluid migration seal, 18-002, 18-072, 18-094, 18-104, 18-154, J18-002, J18-070, J18-108, J18-154
Flammable limits, 18-002, 18-070, J18-002, J18-068
Flashers, signs, 34-114
Flat conductor cable, 12-800

Flexible metal conduit, 12-1002, 12-1004, 12-1010, 12-1302, 12-2002, 12-3022, 34-408, 38-021, Section 0
Floating pier, 78-002, 78-100 to 78-102
Flood elevation, 6-206, 26-712, Section 0
Flood hazard zone, 26-652, 26-712, Section 0
Floodlights, switching of, 30-1020
Flow channel, 64-002, 64-608
Fluid, 18-002, 24-116, J18-002, J18-070
    flammable, 18-066, 18-072, 18-094, 18-154, J18-154
Flush boxes and cabinets, 12-3016
Flux, soldering, 2-118
Footlights, 44-300
Forming shell, 68-050, 68-058, 68-060, 68-066, 68-100
Fuel cell, 64-002, 64-700 to 64-706
    location of, 64-710
Fuel cell system, 64-002, 64-700, 64-702, 64-704, 64-706, 64-710 to 64-716
Full load rating, 36-204, 64-002
Functionally-grounded photovoltaic system, 64-002, 64-064
Fuseholders, 14-206
    signs, 34-114
    size of, 28-208
Fuses
    high-voltage, indoors, 36-206
    installation of, 26-140
    low-melting point, 14-200, 14-610
    non-interchangeable, 14-204
    plug, 14-202
    rating of, 14-208
    time-delay (Type D), 14-200, 14-610
    use of, 14-212
Fusible equipment, 26-142

G

Garages, commercial repair, 20-100 to 20-112
Gasoline dispensing, 20-002 to 20-014
Gates for fences, 26-310
General-use switch, 14-508, 14-510, 14-512, Section 0
Generators
    balancer sets, 28-906
    mobile, 10-214
    not driven by electricity, 28-904
    portable, 10-214
    protection and control, 28-900 to 28-908
    vehicle mounted, 10-214
Grid bus rail, 12-2302, 12-2316
Ground, definition of, Section 0
Ground counterpoise, 74-008, 74-010
Ground electrode, Section 0
    connections, 10-118, 36-308

 © 2021 Canadian Standards Association

high-voltage, 36-308
resistance, 36-304
Ground fault, 10-002, 10-400, 64-064, Section 0
Ground fault circuit interrupter, Class A (Class A GFCI), 2-140, 26-704, 26-710, 30-320, 62-130, 62-408, 64-314, 68-056, 68-064, 68-066, 68-306, 72-108, 76-016, Section 0
Ground fault circuit interrupter (GFCI), 32-200, 38-023, 38-024, 38-085, 58-016, 58-308, 68-068, Section 0
Ground fault detection, 10-400, Section 0
Ground fault protection, 14-102, 32-312, 34-302, 62-116, 84-016, Section 0
location, 14-102, Diagram 3
Ground grid conductor, 36-002, 36-300, 36-302
Grounded, definition of, Section 0
Grounded conductor, 4-018, 4-032, 10-002, 10-004, 10-106, 10-114, 10-210, 10-212, 12-108, 14-016, 26-264, 28-602, 30-1022, 60-706, 64-056, 64-060, 64-064, 64-914, 66-400
Grounding, Section 0
ac systems, 10-206
of antennas, 54-922
circuits, 30-1022
communication systems, 60-700 to 60-710
community antenna distribution systems, 54-200, 54-300 to 54-304
dc systems, 10-200, 10-204
diagnostic imaging equipment, 52-010
electrodes, 10-102, 54-302, 54-910, 60-706, 64-068, Table 43
connection, 54-304, 60-708
interconnection of, 10-104, 60-708
fences, 36-312
high-voltage, 36-300 to 36-312
lighting arresters, 30-1028
lighting equipment, 30-112
objectives, 10-002
pools, 68-058
radio and television stations, 54-900 to 54-922
systems, 10-100 to 10-118
transmitters, 54-1002
Grounding and bonding conductors, 10-112, 10-610, 78-058
connections, 10-118, 10-204, 10-210, 10-212, 10-214, 10-402, 10-600
installation, 10-116, 10-610, 10-612
objectionable current over, 10-100
sizes, 10-114, 10-616, 36-300, 36-308, Tables 16, 41, 43
Grounding conductor, 10-102, 10-112, 10-118, 36-308, 54-300, 54-900 to 54-908, 64-068, Section 0
installation, 10-116
primary protector, 60-704, Table 59
size, 10-114
Grounding system, 60-700 to 60-710, Section 0
GTO sleeving, 34-002, 34-400, 34-402
Guarded, definition of, Section 0
Guarding
bare live parts, 2-202
contact conductors, 40-020

high-voltage parts on diagnostic imaging equipment, 52-004
live parts, 36-110
motors, 28-012, 28-014
Gutters, auxiliary *See* Auxiliary gutters
Guy wire, 64-002, 64-312

H

Hangars, aircraft, 20-400 to 20-422
Hazard index, 24-002, 24-206
Hazardous areas
natural gas, 20-062, Annex J20-062
propane, 20-034, Annex J20-034
Hazardous location, 16-008, 18-000, 18-002, 18-004, 18-010, 18-060, 18-062, 18-066, 18-102, 20-102, 20-202, 20-302, 20-402, 38-042, 54-104, 60-106, 62-318, J18-000, J18-010, J18-060, J18-062, J18-066, J20-062, J20-102, J20-302, J20-402, Section 18
adjacent to openings in a closed spray booth or room, Diagram 10, Diagram JD-10
bonding in, 18-074, J18-072
bulk storage plants, J20-202, Tables 69, JT-69
classified using Division system, Annex J18
communication circuits in, 60-106
container filling outdoors in open air, Diagram 9, Diagram JD-9
definition of, Section 0
division system, Appendix J
documents applicable to, Table B18-1
equipment above, J20-110
equipment in Class II, Division 1, J18-200
equipment in Class II, Division 2, J18-250
equipment in Class III, Division 1, J18-300
equipment in Class III, Division 2, J18-350
equipment not within, 20-408, J20-408
equipment protection level, 18-052, 18-100, 18-150, Appendix
flexible cords in, 18-110, 18-158, 18-196
impedance heating requirements, Table 70
luminaires in, 18-108, 18-156, J18-218, J18-268, J18-316, J18-366
maintenance in, 2-302
marking for, 18-052
NGV fuelling facilities, Table 64
open-face spray booths, Diagram 4, Diagram JD-4
for propane vehicle fuel dispensers, container filling and storage, Tables 63, JT-63
pumps, vapour compressors, gas-air mixers, and vaporizers outdoors in open air, Diagram 8, Diagram JD-8
sealing, 18-104, 18-154, 18-194, 18-254, J18-206, J18-256
separation of, 18-058
spraying operations not conducted in spray booths, Diagram 5, Diagram JD-5
surge protection for, 18-060
switches in, J18-208, J18-258, J18-306, J18-356
tank vehicle and tank car loading and unloading, Diagram 7, Diagram JD-7
trace heating, 62-318, 86-404
transformers in, 18-150, J18-202, J18-252, J18-302, J18-352

 © 2021 Canadian Standards Association

ventilation system interlocked, spraying operations not conducted in spray booths, Diagram 6, Diagram JD-6
wiring above, 20-106, J20-106
wiring and equipment above, 20-206, 20-312, J20-206, J20-312
wiring and equipment in, 20-104, 20-204, 20-306, 20-404, J20-064, J20-104, J20-204, J20-306, J20-404
wiring not within, 20-406, J20-406
zones, Section 18
Hazardous location cable, 18-002, 18-102, 18-192, 18-202, 18-252, J18-106, J18-152, J18-204, J18-254, J18-304, J18-354
HDPE
conductors in conduit, 12-1250
conductors-in-conduit, Section 0
conduit, 12-1250, Section 0
Head, 64-002
Header, definition of, Section 0
Health care facility, 24-002, 24-102, 24-302, 24-306
Health care facility administration, 24-002, 24-102, 24-302
Heating
fixture installation, 62-302
skin effect, 62-314
surface, 62-300
temperature control, 62-120, 62-202
terminal connections, 62-108
Heating cable *see* Trace heater
Heating cable set *see* Trace heater set
Heating device, 62-102, 62-106, 62-108, 62-110, 62-112, 62-114, 62-118, 62-130, 62-204, 62-406
installation of, 62-104, 62-132
usage marking, Table B62-1
Heating device set, 62-102, 62-108, 62-110
non-heating leads of, 62-128
Heating fixture, 62-102, 62-114
installation of, 62-210
Heating panel, 62-102, 62-212, 62-304
below heated surface, 62-304
Heating panel set, 62-102, 62-114, 62-116, 62-202
under floor coverings, 62-218
in gypsum board and other cementitious ceiling and wall installations, 62-216
installation of, 62-212
location of, 62-208
on non-metallic pipes, ducts, or vessels, 62-308
within pipes, ducts, or vessels, 62-400
on tanks, vessels or pipes, 62-310
Height of luminaires, 30-314
Hermetic equipment, 28-700
overcurrent protection for, 28-708
overload protection for, 28-710
Hermetic refrigerant motor-compressor, 28-010, 28-700
High-voltage

see also Voltage
definition of, Section 0
Hoists, Section 40
Hoistway, 38-021, 38-024, 38-037, 60-312, Section 0
Homes
factory-built, Section 70
mobile, Section 70
Hospitals *See* Health care facility
Hydraulic turbine, 64-002, 64-502
Hydrokinetic power system, 64-002, 64-060, 64-600 to 64-610
Hydrokinetic turbine electrical system, 64-002, 64-600, 64-606
Hydrokinetic turbine generator, 64-002, 64-602
Hydrokinetic turbine generator terminal, 64-002, 64-602
Hydromassage bathtub, 68-050, 68-068, 68-300 to 68-308

I

Identified, definition of, Section 0
Identified terminals, connection to, 26-002
Ignition systems for gas turbines, J18-116
Illumination
equipment, 2-320
vaults, 26-356
Impedance grounded system, 10-004, 10-200, 10-206, 10-214, 10-300 to 10-308, Figure B10-12, Table 17
metering requirements for, 6-412
Impedance heating, 62-102, 62-316, Figure B62-7, Table 70
Impedance system bonding jumper, 10-004, 10-308
Inaccessible, definition of, Section 0
Indicating switch, 26-746, Section 0
Induction heating, 62-102, 62-406
Industrial establishment, definition of, Section 0
Infrared radiant heater, 62-102, 62-116
metal-sheath glowing element type, 62-102, 62-220
Inspection
application for, 2-006
availability of work for, 2-028
notification regarding, 2-012
Inspection department, definition of, Section 0
Inspector, definition of, Section 0
Installation
airport, Section 74
of batteries, 64-800 to 64-820
circuit breakers, 26-120
community antenna distribution systems, Section 54
diagnostic imaging equipment, Section 52
fuses, 26-140
heating
fixtures, 62-302
heating panel sets, 62-212

 © 2021 Canadian Standards Association

trace heater sets, 62-124, 62-212, 62-400
optical fiber cables, Section 56
outdoor, 26-008, 36-212
radio and television, Section 54
reinspection of existing, 2-020
sauna heaters, 62-222
Installed capacity, 64-002, 64-510, 64-604
Instantaneous-trip circuit breaker, definition of, Section 0
Insulated, definition of, Section 0
Insulated conductor, 12-302 to 12-306, 12-908, 12-3034, 28-706, 64-212, 64-308, 64-506, 64-606, 64-906, 64-908, Section 0
Insulating, as applied to non-conducting substances, definition of, Section 0
Insulating end, 12-802, 12-808, 12-810, 12-812
Insulation
conductors, 38-011
integrity, 2-138
neutral conductors, 4-016
thermal, 2-126
Insulators, 30-1104
Interactive inverter, 64-002, 64-104, 64-108, 64-112, 64-820
Interactive system, 64-002, 64-072, 64-078, 64-106, 64-110, 64-112
loss of power, 64-078
Interconnection
ground electrodes, 10-104, 60-708
power production sources, Section 84
Interference, 2-032
suppressors, 54-920
Interlocking, 36-208
on transmitters, 54-1004
Intermediate care area, 24-002
bonding to ground in, 24-112
circuits in, 24-110
receptacles in, 24-114
Intermittent duty, definition of, Section 0
Interpretations, Appendix I
Intrinsically safe, 18-066, Section 0
Intrinsically safe circuit, 18-002, 18-092, J18-002
Intrinsically safe electrical system, 18-002, 18-066, J18-002, J18-066
descriptive system documents for, Appendix F
Inverter input circuit, 64-002, 64-060, 64-066, 64-100, 64-924
Inverter output circuit, 64-002, 64-100, 64-924
Isolated system, 10-214, 24-002, 24-110, 24-116, 24-200 to 24-208
Isolating switch, 26-100, Section 0
see also Switch

J

Jacket, definition of, Section 0
Joints
cable trays, 12-2204

expansion of, 12-1118
in rigid contact conductors, 40-016
in sheathed cables, 36-114
Junction boxes, accessibility of, 12-3014

L

Ladder cable tray, Section 0
see also Cable tray
Lampholders, Section 0
connections, 30-600
protection, 30-1114
types, 30-1112
wet or damp locations, 30-606
Landscape lighting system, 30-002, 30-1204
Large wind system, 64-002, 64-400 to 64-412
Layering correction factor, Table 12D
Leakage current collector, 68-050, 68-406
Life safety systems, 46-002, 46-108, 46-208, 46-210
Lighting
circuits, protection of, 30-104
equipment
grounding of, 30-112
installation, Section 30
fixtures *See* Luminaires
outline, Section 34
in proximity to combustible materials, 30-200
Lighting systems
cable, 30-1206
extra-low-voltage, 30-1200 to 30-1208
landscape, 30-1204
Lightning arresters, 26-400 to 26-410
grounding of, 36-308
installation of, 30-1028
receiving stations, 54-800
transmitting stations, 54-802
Lightning conductors
down conductors, 10-108, 12-016
near communication conductors, 60-516
near community antenna distribution systems, 54-608
Lightning protection ground electrode, 10-108
Line isolation monitor, 24-002, 24-204, 24-206
Liquid-filled equipment
indoors, 26-010
outdoors, 26-012
Liquid-tight flexible conduit, 12-1300 to 12-1308, 58-200, Section 0
Live *see* Energized
Live parts, 38-004, Section 0
Livestock, 10-700, 22-802
farm buildings housing, 22-800 to 22-808

 © 2021 Canadian Standards Association

Load
ballast, 64-002
basic, 8-002, 8-200 to 8-210
calculated, 8-002, 8-104, 8-106, 8-202, 26-258
demonstrated, 8-002, 8-106
diversion, 64-002, 64-318, 64-510, 64-600, 64-604, 64-820, 64-922
Load connector, 12-2302, 12-2316
Load factor, 4-004
Locations
motors, 28-304
panelboards, 26-600
resistance devices, 26-550
storage batteries, J18-326
Locked rotor current rating, 28-010, 28-704, 28-712, 28-714, 28-810, 28-812
Long-time rating, 52-002, 52-008
Low-energy power circuit
see also Circuit
definition of, Section 0
Low-voltage
see also Voltage
definition of, Section 0
Low-voltage protection, definition of, Section 0
Low-voltage release, definition of, Section 0
Lower flammable limits, 18-002, 18-070, J18-002, J18-068
Luminaires, Section 0
clothes closets, 30-204
combustible material, 30-200
conductors, colour coding of, 30-402
control of, 30-710, 30-804
damp or wet locations, 30-318, 30-320
discharge type, 30-700, 30-800
disconnecting means, 30-308
equipment, 30-200 to 30-204
exposed to flying objects, 30-316
hazardous locations, 18-108, 18-156, J18-218, J18-268, J18-316, J18-366
height of, 30-314
infrared drying, 62-404
live parts of, 30-300
marking of, 30-822
outdoors, 30-1000, 30-1100
wiring methods for, 30-1004, 30-1006, 30-1100 to 30-1120
polarization of, 30-110
poles, 30-1006
pools, 68-066
raceways, 30-310
recessed, 30-900 to 30-912
show-windows, 30-202, 30-410
support of, 30-302, 30-818
terminals for, 30-820

totally-enclosed gasketed, 30-322
transformers for, 30-806 to 30-812
wiring of, 30-400, 30-406, 30-410, 30-814

M

Machine tool, metal cutting, definition of, Section 0
Machine tool, metal forming, definition of, Section 0
Maintenance
access for, 2-314
live equipment, 2-306
requirements for, 2-300
Manufactured wiring system, 12-2500, 12-2502, Section 0
Marina wiring, 78-056
Marine wharf, 78-002, 78-100 to 78-102
Marking
busways and splitters, 12-2016
Class 2 power supply, 16-204
enclosures, 2-402
luminaires, 30-822
motor compressors, 28-702
motors, 2-404, 28-202
renewable energy source, 64-072
service boxes, 6-214
transformers, 26-262
warning and caution, 2-102
wireways, 12-2112
Maximum ground fault current, 36-002, 36-304, 36-308
Mechanical governor, 64-002, 64-510
Messenger cables, 12-320, 30-1116, 30-1118
Metal raceways, 12-944
Metal tape, 12-802, 12-822
Metering, impedance grounded systems, 6-412
Micro-hydropower systems, 64-002, 64-500 to 64-512
battery-based micro-hydropower system, 64-002, 64-510
Midways, Section 66
Mineral-insulated cable, 6-304, 12-700 to 12-718, Section 0
Mobile home, Section 0, Section 72
size of conduit, Table 48
Mobile home parks, 72-102
Mobile industrial or commercial structure, 2-318, Section 0
Momentary rating, 52-002, 52-008
Monopole, 64-002, 64-056
Motor, Section 28
branch circuit overcurrent protection, 28-200
circuit interrupters, 28-200
circuits, capacitors for, 26-218
conductor ampacity, 28-104 to 28-112, Table D16
conductor sizes
for different requirements of service, Table 27

 © 2021 Canadian Standards Association

in secondary circuits, Table 28
controls, 28-500 to 28-502
currents, Tables 44, 45, D2
disconnecting means, 28-600 to 28-604
feeder conductors, 28-110
feeder overcurrent protection, 28-204
grouping of, 28-206
guarding of, 28-012, 28-014
location, 28-012, 28-014
marking of, 2-404, 28-202
multi-winding, 28-800
overcurrent protection, 28-200 to 28-206, Tables 29, D16
overheating protection, 28-314 to 28-318
overload protection, 28-300 to 28-312, Table D16
part-winding-start, 28-800
portable, 28-102
secondary conductors for, 28-112
supply conductors, 28-104, Table 37
undervoltage protection, 28-400
ventilation of, 28-016
wiring for, 28-100
Motor-circuit switch, 28-602, Section 0
Motor controller, 26-218, 28-200, 28-212, 28-500, 28-506, 38-002, 58-310
Mounting stake, 74-002, 74-010
MSG, definition of, Section 0
Multi-outlet assemblies, 12-3028, Section 0
Multi-winding motor, 28-800, Section 0
Multi-wire branch circuit
see also Circuit
definition of, Section 0
Multiple-section mobile unit, definition of, Section 0
Multitap, 54-002, 54-102

N

Nacelle, 64-002, 64-312, 64-408
Natural gas, compressed, requirements for, 20-060 to 20-070
Neon supply, 34-002, 34-102, 34-200, 34-300 to 34-312, 34-400, 34-404, 34-408
Neutral, Section 0
bare, for services, 6-308
conductors
ampacity, 64-108
common, 4-020
identification of, 4-024, 4-026, 4-028
installation of, 4-022
insulation of, 4-016
joints in service, 6-310
size of, 4-018
Non-combustible construction, 12-602, Section 0
Non-conductive dust, 18-002, J18-002

 © 2021 Canadian Standards Association

Non-continuous duty motor, 28-010
Non-continuous duty service, 28-010, 28-106, 28-108, 28-112
Non-incendive circuit, definition of, Section 0
Non-incendive field wiring circuit, 18-002, 18-066, J18-002, J18-066
descriptive system documents, Appendix F, J18-002
Non-relocatable structure, definition of, Section 0
Non-residential use energy storage system, 64-002
Non-ventilated cable tray
see also Cable tray
definition of, Section 0
Normal operation, 10-100, 10-500, 18-002, 18-070, J18-002
Normal supply, 24-002, 24-304, 46-000
Number of outlets per circuit 8-304

O

Open, as applied to electrical equipment, definition of, Section 0
Openings, unused, in boxes, cabinets and fittings, 12-3024
Operating device, 38-002, 38-036, 58-104, 58-200
Operation, requirements for, 2-300
Optical fiber cables, 56-100, Section 56
air ducts or plenums, 56-210
Ordinary location, definition of, Section 0
Organs, pipe, 26-900
Outdoor floodlighting, 30-1000 to 30-1030
Outdoor installations, 26-012, 36-212
Outdoor location, definition of, Section 0
Outlet, definition of, Section 0
Outlet boxes, 12-3000, 30-304
covers, 12-3002
in damp places, 12-3020
not required, 12-522
supports, 12-3010
Outlet branch-circuit-type arc-fault circuit interrupter, 26-650, 26-658
Outlets, maximum number per circuit, 8-304
Outline lighting, Section 0, Section 34
Overcurrent devices, 14-100, 14-104 to 14-114, 26-210, 28-708, 30-108, 30-1114, 30-1120, 34-310, 36-204, 40-006, 46-208, Section 0, Table 13
accessibility of, 14-106
in parallel, 14-112
Overcurrent protection, 14-100, 36-204, 40-006
apparatus and conductors, 64-214
arc welders, 42-008
capacitors, 26-210
Class 1 circuits, 16-104 to 16-108
Class 2 circuits, 16-206, 16-208
elevators, 38-061
emergency systems, 46-208
fire pumps, 32-306
heating, 62-114

 © 2021 Canadian Standards Association

lampholders, 30-1120
motor branch circuits, 28-200
motor feeders, 28-204
motors, 28-200, 28-202, Table D16
neon supply, 34-310
panelboards, 14-606
photovoltaic systems, 64-214
pole top circuits, 30-1010
refrigerant motor-compressors, 28-708
resistance welders, 42-016
setting, 14-104, 28-204, Tables 13, D16
theatres, 44-210
transformers, 26-250 to 26-254, 30-1018, Table 50
Overload device, 28-302, Section 0, Table 25
Overload protection, 28-300 to 28-312, 28-710

P

Panelboard, 26-600 to 26-602, Section 0
enclosed, Section 0
location, 26-600
overcurrent protection for, 14-606
Parallel heating cable set *see* Trace heater set
Parallel trace heater, 62-102
Park model trailer, definition of, Section 0
Parks for mobile homes and recreational vehicles, Section 72
Part-winding start motor, definition of, Section 0
Passenger conveyor, 58-002, 58-302
Passenger ropeways, Section 58
Patient, 24-002, 24-116, 24-300
Patient care area, 24-002, 24-100 to 24-116
Patient care environment, 24-002, 24-102, 24-104, 24-200, 24-204
Patient care environment bonding point, 24-002, 24-112
Pendant connector, 12-2302, 12-2316
Periodic duty, definition of, Section 0
Permanently connected equipment, definition of, Section 0
Permanently installed swimming pool, 68-050, 68-100
Permit, 2-004, Section 0
current-, 2-016
posting of, 2-010
Photovoltaic combiner, 64-002, 64-060
Photovoltaic dc arc-fault circuit protection, 64-216
Photovoltaic module, 64-002, 64-214, 64-216
Application Class A photovoltaic module, 64-002, 64-208
Application Class B photovoltaic module, 64-002, 64-208
Application Class C photovoltaic module, 64-002, 64-208
bonding, 64-060, 64-222
Photovoltaic output circuit, 64-002, 64-060, 64-200, 64-204, 64-212
Photovoltaic power source, 64-002, 64-202
Photovoltaic recombiner, 64-002, 64-060

 © 2021 Canadian Standards Association

Photovoltaic source circuit, 64-002, 64-200, 64-202, 64-204, 64-210, 64-212, 64-214, 64-222
Photovoltaic system rapid shutdown, 64-218
Pipe organs, 26-900
Pipeline impedance heating, 62-316
Plans and specifications, 2-014
Plenum, definition of, Section 0
Plug-in hybrid electric vehicle (PHEV), 86-100
Point of common coupling, 64-002, 64-078, Figure B64-6
Point of distributed resource connection, 64-002
Polarization of luminaires, 30-110
Pools, tubs, and spas, Section 68, Table 61
Portable, as applied to electrical equipment, definition of, Section 0
Portable fuel cell system, 64-002
Portable ground fault circuit interrupter, definition of, Section 0
Portable lamps, hazardous locations, 18-156
Portable power cables, 12-406
Postponement, 2-030
Posts for fences, 26-308, 26-316
Potential rise of ground grid, 36-002, 36-304
Power blocking device, 54-002, 54-102
Power conditioning unit output circuit, 64-002
Power conditioning unit (PCU), 64-002, 64-112, 64-204, 64-212
Power electronics input, 64-002, 64-602
Power feed connector, 12-2302, 12-2316, 12-2318
Power sourcing equipment, 16-300, 16-310, 16-320, 16-330, 16-350
Power supply cord, 70-108, Section 0
Powered device, 16-300, 16-310
Pressurized equipment, 18-064
Primary process seal, 18-002, 18-072, J18-002, J18-070
Process seal, 18-002, 18-072, Figure B18-1, Figure JB18-1, J18-002, J18-070
Propane, J20-032
Protected, as applied mainly to electrical equipment, definition of, Section 0
Protection
- arc-fault, 26-650, 26-658, 64-210, 64-216
- ballast, for signs, 34-104
- communication circuits, 60-200 to 60-204, 60-504
- conductors, 12-100, 40-004, 40-006
- connection of devices, 14-016
- against corrosion, 2-116
- generators, 28-902
- ground fault, 14-102
- lampholders, 30-1114
- lighting circuits, 30-104
- mechanical
  - of armoured cable, 12-604
  - of NMSC, 12-514 to 12-518
- overcurrent, 14-100, 28-200, 28-708, 36-204, 40-006
  - arc welders, 42-008
  - elevators, 38-061

 © 2021 Canadian Standards Association

emergency power supply, 46-208
heating, 62-114
motor compressor, 28-708
panelboards, 14-606
resistance welders, 42-016
overheating, of motors, 28-314 to 28-318
overload
for motor compressor, 28-710
of motors, 28-300 to 28-312
persons, 2-200
property, 2-200
receptacles, 14-600
setting, 14-104, 28-204, Tables 13, D16
shock and flash, 2-306
theatres, 44-210
type of, 18-002, 18-050, 18-076, J18-002
underground conductors, 12-012, Table 53
undervoltage, 28-400
Protective devices
rating of, 14-012
required, 14-010
Protective gas, 18-002, 18-064, J18-002, J18-064
Protector plate, 12-516
Pull box size, 12-3036
Pumps
pools, 68-202
submersible, 26-950 to 26-956
PVC conduit *see* Conduit

Q

Qualified person, definition of, Section 0
Quality of work, 2-112

R

Raceways, Section 0
cellular floor *See* Cellular floors
conductors in, 12-904 to 12-910, 12-914
consumer's service, 6-306
fittings for underfloor, 12-1704, 12-1708, 12-1710
flat cable systems in surface, 12-1614
in roof decking systems, 12-022
installed before conductors, 12-938
number
of bends, 12-942
of conductors in underfloor, 12-1714
protection of, 12-934, Table 53
radii of bends, 12-924
surface, 12-1600 to 12-1614
in post- and pre-stressed floors, 12-1718

 © 2021 Canadian Standards Association

through walls and floors, 12-1602
underfloor, 12-1700 to 12-1718
underground, 12-930, Table 53
Radio noise suppressors, 54-920
Rail, 12-2302, 12-2316, 38-034, 40-018
Rail-to-rail connector, 12-2302, 12-2316
Ranges, electric, 8-300, 26-744
Rated load current, 28-010, 28-702, 28-706, 28-710, 28-712, 28-714
Rated power, 64-002, 64-100, 64-500, 64-600, 64-924
Rated primary current, 26-250, 26-252, 26-254, 26-256, 26-266, 42-002
Readily accessible, definition of, Section 0
Receptacles, 26-700 to 26-724, 26-744, 76-016, Section 0
configurations, 26-654, 26-700, 26-708, 26-720, 26-744, Diagram 1, Diagram 2
cord-connected hydromassage bathtubs, 68-306
for dwelling units, 26-722
heater, for flammable or combustible fuel powered vehicles, 8-400
for maintenance of equipment, 2-316, 26-710
pipe organs, 26-900
pools, tubs, and spas, 68-064, 68-202, 68-306, 68-404
protection of, 14-600
residential occupancies, 26-720 to 26-724
for single dwellings, 26-724
tamper resistant, 26-706
Recessed luminaire, 30-002, 30-900 to 30-912
Type IC, 30-002, 30-906
inherently protected, 30-002, 30-906
Type Non-IC, 30-002, 30-902
marked spacings, 30-002, 30-904
Reconnection, 2-018
Recreational vehicle, 72-108, Section 0
Recreational vehicle lot, 72-002, 72-104, 72-108, Table 71
supply equipment, 72-002, 72-102, 72-112
Recreational vehicle parks, Section 0, Section 72
Recreational vehicle stand, 72-002, 72-102, 72-112
Refrigerant motor-compressor, 28-010, 28-700 to 28-714
Reinspection, 2-020
Rejection, powers of, 2-026
Relocatable structures, 70-100 to 70-130, Section 0
Remote control circuit
see also Circuit
definition of, Section 0
Renewable energy, 64-002, 64-054, 64-062, 64-064, 64-070, 64-818
Renewable energy system, 64-002, 64-052, 64-058, 64-060, 64-066, 64-068, 64-074, 64-076, 64-078, 64-100, 64-102, 64-110, 64-210, 64-316, 64-820
with storage, Figure B64-2
typical, Figure B64-1
Requirements, special, 2-002
Residential occupancy, 62-114, Section 0
Residential use energy storage system, 64-918

 © 2021 Canadian Standards Association

Resistance devices, 26-550 to 26-554
Resistant, used as a suffix, Section 0
Reverse polarity protection (back-feed protection), 12-2302
    output connections and, 12-2318
Rigid conduit, 12-2002, 12-2108, 28-100, 68-100, Section 0
Rigid metal conduit, 12-1002, 12-1006, 12-1010, 18-092, J20-006, Section 0, Table 40
Rigid non-metallic conduit, 32-302, 46-108, Section 0
Rigid PVC conduit, 12-1100 to 12-1124, Section 0
Rigid RTRC conduit Type AG, 12-1200, 12-1202, 12-1216, Section 0
Rigid RTRC conduit Type BG, 12-1200, 12-1202, Section 0
Rigid RTRC conduit Type XW, 12-1200, 12-1202, 12-1216, 18-152, 18-252
Rigid Type DB2/ES2 PVC conduit, 12-1150 to 12-1166, Section 0
Rigid Type EB1 PVC conduit, 12-1150 to 12-1166, Section 0
Rinks, 22-204
Rooftop equipment, 2-316, 26-710
Rules of procedures, Appendix C

S

Sauna heater, 62-102, 62-222
Sealed cell battery, 64-002
Seals, 18-002, 18-072, 18-104, 18-154, J18-002, J18-070, J18-154
    flow chart for selection using cables, Figure B18-2, Figure JB18-2
    flow chart for selection using conduits, Figure B18-3, Figure JB18-3
Secondary process seal, 18-002, 18-072, J18-002, J18-070
Self-contained energy storage system, 64-002, 64-904, 64-910, 64-914, 64-918, 64-920, 64-926, 64-928
Self-protected combination motor controller, 28-200
Seismic restraint,
Semi-hermetic refrigerant motor-compressor, 28-010, 28-700
Semiconductor fuses, 14-112, 28-212
Separate built-in cooking unit, definition of, Section 0
Separately derived system, 10-004, 10-212, 10-402
    at the first switch, Figure B10-8
    grounded at each source, Figure B10-9
    grounding for, operating at 750V or less, Figure B10-11
    at the source, Figure B10-7
    transfer equipment tie point, Figure B10-10
Separation
    Class 2 Circuits, 16-212
    from other conductors, 60-308
Series isolating transformer, 74-002, 74-006, 74-010
Series rated combinations, 14-014
Series trace heater, 62-102, 62-126
Series trace heater set, 62-102
    construction of, 62-122
    field repair, modification or assembly of, 62-126
    installation of, 62-124
Service
    3-wire, 6-110
    consumer's, Section 0

number of, 6-104
subdivision of main, 6-202
service equipment, Section 6
stations, 20-002
supply, Section 0
number of, 6-102
switches, oil-circuit breakers used as, 6-210
terminating conductors, 6-114
underground, 6-300
Watts per square metre and demands factors, Table 14
Service boxes, 6-200, Section 0
fuse enclosure on, 6-204
locked, 6-206
marking of, 6-214
Service conductors, 6-300, 6-302
crawl spaces, 6-208
outside building, 6-208
use of bare neutral for, 6-308
Service equipment, 6-200
high-voltage, 36-212
location, 6-206, 36-200
Service factor, 28-010, 28-306
Service head location, 6-116
Service room, definition of, Section 0
Sewage lift and treatment plants, 22-700 to 22-710
Sheath, Section 0
currents, 4-008
Shielding of conductors, 36-104
Shockproof, 52-004, Section 0
Short-time duty, Section 0
see also Duty
Signal circuit, 16-004, 16-006, 16-012, 58-012, 58-102, Section 0
see also Circuit
Signal equipment, 38-002, 58-200
Signs, 34-002, Section 34
See also Warning notices
ballast protection for, 34-104
bonding, 34-110, 34-408
disconnecting means for, 34-100
enclosure, 34-200
exit, 46-400
location, 34-106
subassemblies, 34-110
supports, 34-108
wiring methods for, 34-400
Single dwelling, definition of, Section 0
Single process seal equipment, 18-002, J18-002
Single receptacle
see also Receptacles

 © 2021 Canadian Standards Association

definition of, Section 0
Skin effect trace heating, 62-102, 62-314, Figure B62-6
Slow-burning, as applied to conductor insulation, definition of, Section 0
Small wind system, 64-002, 64-300 to 64-320
Smoke alarms, 32-200
Solar cell, 64-002
Solar photovoltaic system, 64-002, 64-200 to 64-222
Soldered, definition of, Section 0
Solid-state devices, 14-700 to 14-704
Solidly grounded system, 10-004, 10-200 to 10-214, 10-302, 14-102, 30-1022, 36-308
three-phase, 4-wire, without a bonding conductor, supplied from the supply authority, Figure B10-6
Spa or hot tub, 68-050, 68-068, 68-400 to 68-408
Space, working, 2-308, 38-005
Space heating, 62-200 to 62-222, Table 67
Spacing
of conductors, 12-204, 12-306, 36-108, Tables 30–34
electrodes, 10-104
for switches and fuses, Table 35
Special permission, definition of, Section 0
Specialty-type equipment, 22-802
Specifications, plans and, 2-014
Splash pad, 68-050
Splices
cable trays, 12-2204
wireways, 12-2106
Split receptacle
see also Receptacles
definition of, Section 0
Split straight conduit, 12-1124, 12-1164
Splitter, definition of, Section 0
Splitters, 12-2000 to 12-2020
AC circuits in, 12-2004
manufacturer's identification, 12-2016
restrictions on circuits in, 12-2020
supports, 12-2006
taps in, 12-2018
Spray painting, 20-300
Stand-alone system, 64-002, 64-074, 64-078, 64-102, 64-218, Figure B64-3
Starter, definition of, Section 0
Station, 36-002, 36-006, 36-214, 36-302, 58-002, 58-016
exemption, 36-306
gasoline dispensing, 78-062
grounding of, 58-600 to 58-610
luminaires on, 58-016
outdoor, grounding of metallic fence enclosures of, 36-312, 58-002
Station ground electrode, 36-302
Station ground resistance, 36-304
Stationary fuel cell system, 64-002, 64-700 to 64-716
Step and touch voltage, 36-002, 36-304, 36-306, Table 52

Steps, climbing, 30-1030
Storable swimming pool, 68-050, 68-200 to 68-202
Strandings, Table D5
Structures, factory-built, Section 70
Submersible pump, 26-950 to 26-956
Suitably cut off, 22-700, 22-704, 22-802, J20-004
Sunlight resistance, 2-136
Supervision of fire alarm circuits, 32-106
Supplementary protectors, application of, 14-114
Supply authority, definition of, Section 0
Supply authority system, disconnecting means, 84-022
Supply connections for appliances, 26-744, 26-746
Supply for electric ranges, 8-300
Supply wiring, 60-318, 64-002, 64-304, 64-402, 64-404, 64-502
Supports
- boxes, fittings and cabinets, 12-3012
- busways and splitters, 12-2006
- insulated conductor, 12-204
- luminaires, 30-302, 30-818
- outlet box, 12-3010
- vertical raceways, 12-120, Table 21

Suppressors for interference, 54-920
Surface
- heating, 62-300 to 62-318
- raceways *See* Raceways, surface

Surface raceway, definition of, Section 0
Surge protection in hazardous locations, 18-060
Surge protectors, 26-420
Suspended ceiling grid, 12-2302, 12-2314
Swimming pool
- bonding, 68-058
- luminaires, 68-066
- permanently installed, 68-100
- pumps, 68-202
- storable, 68-200 to 68-202

Switchboards, Section 0
- for theatres, 44-200

Switches, Section 0
- connection of, 14-506
- floodlights, 30-1020
- hazardous locations, J18-208, J18-258, J18-306, J18-356
- horn-gap, 36-212
- isolating, 26-100, 36-214
- luminaire, 30-320
- luminaire canopies, 30-306
- mounting, 14-502
- operation of, 14-500
- rating of, 14-504, 14-508, 14-510
- transfer, 14-612, 32-308

 © 2021 Canadian Standards Association

Switching, control devices used only for, 14-416
System bonding jumper, 10-004, 10-210, 10-212, 10-308, 30-1022, Table 16
size of, 10-616
Systems
communication, electrical, Section 60
supply from more than one, 6-106

T

Tamper resistant receptacles, 26-706
Tap conductor, 26-742, 26-802, 28-106, 62-108
Television installations, Section 54
Temperature correction factor, Table 12B
Temperature limitations, 4-006, 12-1104, 12-1154, 12-1210, 12-1508, 12-1604
Temporary wiring, Section 76
Terminal fittings, 12-3004, 12-3006
Terminals, identified, connection to, 26-002
Terminating facilities, 36-112
Theatre, Section 0, Section 44
Thermal cut-out, definition of, Section 0
Threads, conduit, 12-1006, Table 40
Top shield, 12-802, 12-812
Torques, recommended tightening for screws and connectors, Tables D6, D7
Total hazard index, 24-002
Touch voltage, 36-002, 36-306, 36-308, 36-310, Table 52
Tower, 64-002, 64-306, 64-310, 64-312, 64-400, 64-406, 64-408, 68-054
Trace heater, 62-102, 62-104, 62-126, 62-204
below heated surface, 62-304
Trace heater set, 62-102, 62-114, 62-116, Table B62-1
under floor coverings, 62-218
in gypsum board and other cementitious ceiling and wall installations, 62-216
installation of, 62-212
installed on or wrapped around surfaces, 62-306
location of, 62-208
on non-metallic pipes, ducts, or vessels, 62-308
within pipes, ducts, or vessels, 62-400
in plaster or other cementitious material, 62-214
Transfer switches, 32-308
Transformer continuous load, 26-258
Transformer housing, 74-002, 74-004, 74-010
Transformer rated meter mounting device, 6-100, 6-402
Transformers, 26-240 to 26-266
approved, 60-110
arc welders, 42-006 to 42-010, Table 42A
auto-, 26-264
capacitors, 26-220
conductor size for, 26-256
diagnostic imaging equipment, 52-010
disconnecting means for, 26-248
dry-core, open-ventilated-type, 26-246

 © 2021 Canadian Standards Association

hazardous locations, 18-150, J18-202, J18-252, J18-302, J18-352
location of, for luminaires, 30-812, 30-1016
luminaires, 30-804
marking of, 26-262
oil-filled, 30-702
outdoor, 26-242
overcurrent protection for, 26-250 to 26-254, 30-1018, Table 50
pools, 68-062
roofs, 26-244
Transition assembly, 12-802, 12-816
Transmitter amplifiers, 54-1006
Transmitters, 54-1000 to 54-1006
Travelling shows, 44-100, Section 66
Tubing, internal diameter and cross-sectional areas, Tables 9A, 9B, 9C, 9D, 9E, 9F, 9G, 9H
Turbine speed/load controller, 64-002, 64-310
Type FCC cable, 12-802, 12-808, 12-812, 12-820, 12-822
Type FCC cable connector, 12-802, 12-810, 12-812
Type FCC system, 12-802, 12-804, 12-806, 12-812, 12-814, 12-816, 12-818, 12-822, 60-330

U

Unbalanced interconnections, 64-110
Under-carpet cable, 12-800, 60-322
Undercabinet lighting system, 30-002, 30-1208
Underfloor covering, heating panel sets, 62-218
Underfloor raceway, 12-1700 to 12-1718, Section 0
Underground
ampacity, 4-004
Class 2 circuits, 16-226
communication conductors, 60-600 to 60-604
services, 6-300
Undervoltage protection, 28-400
Ungrounded system, 10-004, 10-214, 10-400 to 10-402, Figure B10-13
Unit equipment, 46-002, 46-300 to 46-306
Upper flammable limits, 18-002, 18-070, J18-002, J18-068
Utilization equipment, definition of, Section 0

V

Varying duty
see also Duty
definition of, Section 0
Vault illumination, 26-356
Vaults, 26-350 to 26-356, Section 0
Vehicle charging systems, electric, Section 86
Vehicle fuel dispenser, 20-032
propane, hazardous areas for, Table 63
Ventilated cable tray, Section 0, Table D17M
see also Cable tray
Ventilation
cooking equipment, 26-750

 © 2021 Canadian Standards Association

equipment, 2-322, 20-304
motors, 28-016
Vessel, definition of, Section 0
Vital branch, 24-002, 24-302, 24-304
Voltage, 30-102, 30-1022
Class 1 Circuits, 16-100
Class 2 Circuits, 16-200
conductors, 12-502
current calculations, 8-100
drop, 8-102, 64-204, Tables D3, D4
dwelling units, 2-110, 30-102, 30-706, 30-802
high-, Section 36
on diagnostic imaging equipment, 52-004
lighting equipment, 30-102
limitations, 38-003, 54-102
neon supplies, 34-300
ratings of cables and conductors, Table D1
step, 36-002, Table 52
touch, 36-002, Table 52
Voltage-to-ground, 2-110, Section 0

W

Warning notices, 14-414, 14-704, 36-006, 80-014, 84-030, 86-200, Appendix M
Wash-down, 22-802, 22-806
Washroom, definition of, Section 0
Welders
arc, 42-006 to 42-010, Table 42A
inverter, 42-006 to 42-010, Table 42A
motor-generator, 42-012, Table 42B
resistance, 42-014 to 42-020, Table 42C
Wet location, Section 0
Wet-niche luminaire, 68-050, 68-100
Wet well, 22-700, 22-704, 22-708
Wharves, Section 78
Wind turbine, 64-002, 64-300, 64-304, 64-308, 64-310, 64-314, 64-402, 64-404, 64-406, 64-410
Wind turbine electrical system, 64-002
Wind turbine generator (WTG), 64-002, 64-406
Wind turbine generator (WTG) system, 64-002, 64-406
Wind turbine terminal, 64-002
Wire
barbed, 26-306
equipment, 12-122
guy, 64-002, 64-312
Wire connector
see also Connector
definition of, Section 0
Wireways, 12-2100 to 12-2112, Section 0
Wiring
above hazardous areas, 20-206

 © 2021 Canadian Standards Association

conductors for Class 2 circuits, 16-210
ducts and plenums, 12-010, 16-220, 60-314
fire alarms, 32-102
marinas, 78-056
method, Section 12
elevators, 38-021
emergency systems, 46-108
hazardous locations, 18-102, 18-152, 18-192, 18-202, 18-252, J18-204, J18-254, J18-304, J18-354
high-voltage, 34-400, 36-100
motors, 28-100
passenger ropeways, 58-200
signs, 34-400
theatres, 44-102
natural gas refuelling stations, 20-064
pools, 68-100
propane, 20-036
space, 30-306
in enclosures, 6-212, 12-3032
systems
manufactured, 12-2500, 12-2502
underground, 12-012
temporary, Section 76
Wood, use of, 26-314
Work, quality of, 2-112
Working space/clearance, 2-308, 38-005

X

X-ray *See* Diagnostic imaging equipment

Z

Zero sequence filters, 26-266
Zone 0, 18-002
acceptable equipment protection levels, Table B18-5
area classification, 18-006
equivalency between Division area classifications and, Table B18-2
installations in, 18-090 to 18-094
typical oil water sump, Figure B18-4
Zone 1, 18-002, 20-004, 20-302
acceptable equipment protection levels, Table B18-5
area classification, 18-006
equivalency between Division area classifications and, Table B18-2
installations in, 18-100 to 18-110
Zone 2, 18-002, 20-004, 20-302, 20-420
acceptable equipment protection levels, Table B18-6
area classification, 18-006
equivalency between Division area classifications and, Table B18-2
installations in, 18-150 to 18-158
Zone 20, 18-002

 © 2021 Canadian Standards Association

equivalency between Division area classifications and, Table B18-2
installations in, 18-190 to 18-196
Zone 21, 18-002
equivalency between Division area classifications and, TableB18-2
installations in, 18-200 to 18-204
Zone 22, 18-002
equivalency between Division area classifications and, Table B18-2
installations in, 18-250 to 18-254

 © 2021 Canadian Standards Association